

# RT381-SP | Rotary Temperature Transmitter

TempTrak® All-Digital Technology  
For Precise Godet Temperature Control

The RT381-SP is a one-channel temperature measurement system designed as an upgrade for Teijin-Seiki STA transmitters to monitor and control temperature on heated godet roll shells on filament spinning machines. The system features generous 10 mm clearance between the rotating and stationary parts which eliminates damage due to impact and rubbing. TempTrak® data communications technology is unaffected by dust or debris. Digital circuitry in the rotating transmitter and the stationary receiver are immune to electrical noise and drift. Fault detection modes protect heater from damage and expedite troubleshooting in the event of a sensor failure.



- Generous 10 mm rotor-stator clearance
- Replacement for Teijin-Seiki STA
- Digital circuitry from sensor input to signal output

## FEATURES

**Accurate** ■ Within  $\pm 0.5^{\circ}\text{C}$  across entire sensing range.

**Robust** ■ Fully encapsulated electronics with generous clearance between rotor and stator.

**Fully Compatible** ■ Easy replacement, works with existing wiring and process control systems for temperature and speed (RPM) signals.

**Digital Circuitry** ■ Maintains calibration and is immune to electrical noise and drift.

**Intelligent** ■ Protects heater if sensor or transmitter malfunctions.

**Product Support** ■ Backed by BEI's reputation for the strongest customer support in the industry including a two-year warranty.

BINSFELD ENGINEERING INC.

Good. Better. Binsfeld.

# RT381-SP Rotary Temperature Transmitter

## TYPICAL SPECIFICATIONS

### Rotor

Number of Sensors:	1
Input Sensor Type:	JPt200 RTD (200 $\Omega$ at 0°C) JIS – Japanese
Speed:	standard 10,000 RPM (max)

### Stator

I/O Connector:	8 conductor screw terminal
I/O Signal - Temperature:	551 to 6959 Hz for -10 to 300°C RTD temperature
I/O Signal - Speed:	16 to 4000 Hz for 80-20,000 RPM
Status Indicator Lights:	Power, Temperature, Signal
Supply Voltage:	18 - 28VAC or 25 - 40VDC
Supply Current:	200mA (max), 100mA (nom)
System Accuracy:	$\pm 0.5^{\circ}\text{C}$ (max over operating temperature range)
Operating Temperature:	0 - 85°C

*Specifications subject to change without notice.*

### Warranty

Binsfeld Engineering Inc. warrants that its RT381 Series Transmitters will be free from defective materials and workmanship for a period of two years from the date of delivery to the original purchaser and that its products will conform to specifications and standards published by Binsfeld Engineering Inc. Upon evaluation by Binsfeld Engineering Inc., any product found to be defective will be replaced or repaired at the sole discretion of Binsfeld Engineering Inc. Our warranty is limited to the foregoing. Binsfeld Engineering Inc. disclaims any warranty of merchantability or fitness for intended purpose.



BINSFELD ENGINEERING INC.

Good. Better. Binsfeld.