

RT220 | Rotary Temperature Transmitter

Leading Technology for Godet Rolls

The Binsfeld RT220 Rotary Temperature Transmitter is a true drop-in replacement for Rieter/SwissTex rotating transmitters on high-speed godet roll motors. The RT220 features a rugged mechanical design with fully encapsulated electronics to operate up to 13,000 rpm. In addition, error detection modes protect heater from damage and expedite troubleshooting in the event of a sensor or other failure.

Rugged – Fully encapsulated rotating electronics.

Reliable – Digital circuitry is immune to electrical noise and drift.

Rieter/SwissTex Compatible – Drop-in replacement for J7-30, J7-31 and J7-32 roll motors.

Product Support – Strongest customer support in the industry.



SPECIFICATIONS

Input ■ PT200 RTD (2x PT100 in series)

Input Range ■ 200.00 Ω to 424.06 Ω (0°C to 300°C)

Output ■ Pulsed infrared LED @ 935nm

Output Range ■ 21,731 Hz to 14,935 Hz (0°C to 300°C)

Accuracy

- within $\pm 0.20\%$ 0°C to 85°C ambient
- within $\pm 0.11\%$ 20°C to 70°C ambient

Operating Environment

- 0°C to 85°C, 0-90% RH, non-condensing

Rotational Speed ■ 13,000 RPM maximum

Weight ■ 4 lbs. (1.8 kg)

Error Mode Output

- 14.80 kHz RTD value is too high
- 14.75 kHz RTD value is too low
- 14.70 kHz power supply voltage is too low
- 14.65 kHz power supply voltage is too high
- 14.60 kHz ambient temperature is too high

Specifications subject to change without notice.



BINSFELD ENGINEERING INC.

4571 W. MacFarlane Rd. ■ Maple City, MI 49664 ■ USA
Phone: (+1) 231.334.4383 ■ Fax: (+1) 231.334.4903 ■ Toll Free: 800.524.3327 ■ www.temprak.com

Good. Better. Binsfeld.